



	LOTECHNIK		
×] Item		sugg. retail €
iek	ko fx 26 foldable recumbent trike 20"/26" (GEL)		
	Gekko fx 26 basic model under seat steering. STURMEY ARCHER 24 speed derailleur/hub gears. SHIMANO hydraulic		2 (00.00
	disc brakes		3.690,00
	Gekko fx 26 frameset foldable, with seat, handlebar, front hubs, chain guide setup		2.890,00
iek	ko fx 26 options extra charge – drivetrain and brake options for complete bikes only		
			0,00
			199,00
			0,00
			199,00
			0,00
			49,90
			229,00
	headrest for meshseat adjustable in height and angle, with quick release lever		179,00
	seat angle adapter to adjust the backrest in a more upright position, with quick release		99,90
	Gekko seat pad additional comfortable and breathable upholstered seat pad to attach to the seat, fastening with buckles		169,00
	handrests left and right comfortable hand support, mounted on handlebar, removable cushion		159,00
	adjustable end stops allow exact positioning of the seat		19,90
	add-on bags for meshseat pair mounted on backrest, each 1.4 litres, 1 water-repellent bag, 1 ventilated bag		67,90
	rain cover for seats, ripstop nylon fabric, blue		29,90
	drivetrain STURMEY ARCHER Tripleshift 24 24 speed with twist shifters (basic specification), SRAM X4 rear		
	derailleur, STURMEY ARCHER 3 speed internal hub		0,00
			39,90
			37,70
	drivetrain STURMEY ARCHER Tripleshift 30 30 speed, rear derailleur MICROSHIFT XLE, MICROSHIFT / STURMEY ARCHER barend shifters, STURMEY ARCHER 3 speed internal hub		179,00
			269,00
			1.950,00
			1.990,00
1			1.770,00
	E-drive SHIMANO STEPS E5000 SRAM X4 up to 25 km/h (16 mph), SRAM X4 8-speed rear derailleur, Li-Ion battery 418 Wh, 2 A charger, push assist		1.490,00
	E-drive SHIMANO STEPS E5000 Nexus Di2 up to 25 km/h (16 mph), SHIMANO Nexus 8 speed Di2 gear hub, Li-Ion		
	battery 418 Wh, 2 A charger, push assist		1.790,00
	E-drive SHIMANO STEPS EP5 SRAM X4 up to 25 km/h (16 mph), SRAM X4 8-speed rear derailleur, Li-lon battery		
	418 Wh, 2 A charger, push assist		2.290,00
	E-drive SHIMANO STEPS EP5 Nexus 5 Di2 up to 25 km/h (16 mph), SHIMANO Nexus 5 speed Di2 gear hub, Li-Ion battery 418 Wh, 2 A charger, push assist		2.650,00
	E-drive SHIMANO STEPS EP5 Nexus 8 Di2 up to 25 km/h (16 mph), SHIMANO Nexus 8 speed Di2 gear hub, Li-Ion		2.590,00
3	battery 418 Wh, 2 A charger, push assist		
	E-drive SHIMANO STEPS EP801 Nexus 5 Di2 up to 25 km/h (16 mph), SHIMANO Nexus 8 speed Di2 gear hub, Li-		3.290,00
ή_	Ion battery 418 Wh, charger 2 A, push assist		
	E-drive SHIMANO STEPS EP801 Cargo Cues Di2 up to 25 km/h (16 mph), SHIMANO Cues Di2 10-speed derailleur,		3.390,00
1	Li-Ion battery 418 Wh, charger 2 A, push assist, freeshift and autoshift function		5.570,00
	E-drive SHIMANO STEPS EP801 Cargo ENVIOLO Automatiq up to 25 km/h (16mph), ENVIOLO hub with		4 200 00
	Automatiq internal stepless shifting, Li-Ion battery 418 Wh, 2 A charger, push assist		4.290,00
_	E-drive SHIMANO STEPS EP801 Cargo ROHLOFF up to 25 km/h (16 mph), incl. ROHLOFF 14 gear interneal gear		
	hub, Li-Ion battery 418 Wh, 2 A charger, push assist		4.890,00
1	E-drive NEODRIVES Z20 with SRAM/30 up to 25 km/h (16 mph), 30 gears, rear derailleur SRAM GX, handlebar end		
			3.490,00
	backwards, Display position: O above handlebar O side of handlebar		
	E-drive NEODRIVES Z20 with PINION C1.12 up to 25 km/h (16 mph), front gear box, Li-lon 576 Wh, push assist	<u> </u>	
	forward and backwards, not compatible with streamer, display position: O above handlebar O side of handlebar		5.290,00
			310.00
			319,00
			39,90
		I	24,90
	tire exchange from SCHWALBE Tryker 40 mm / 1.6" to O Marathon Plus 47 mm / 1.8" O Kojak 35 mm / 1.4" (SRAM/30		49,90
	or PINION)		

HP VELOTECHNIK GmbH & Co. KG • Kapellenstr. 49 • 65830 Kriftel • Germany • phone +49 61 92-97 99 2-0 • fax +49 61 92-97 99 2-299 • WEEE-Reg.- Nr. DE65590493 CR Frankfurt/M HRA 47004 • General Partner: HP VERWALTUNG GmbH, Kriftel, Germany, CR Frankfurt/M HRB 112233, Managing Director: Paul Hollants and Daniel Pulvermüller





	×	ltem		su			
				reta			
Ge	_	kko fx 26 accessories Surcharges, additional special accessories on the "comfort and ability options" order form					
		disc brakes SHIMANO BR-MT200 hydraulic, separate brake per front wheel (basic specification)		0			
		disc brakes AVID BB7 mechanical, separate brake per front wheel		69			
ŝ		disc brakes SHIMANO XT hydraulic, separate brake per front wheel, lever reach adjustable		209			
brakes		disc brakes AVID BB7 coupled front brakes, mechanical, rear disc brake, parking brake function front brake lever: O left O right		189			
ē		hydraulic disc brakes RIDEREVER coupled hydraulic, coupled front brakes with one-hand operation and parking brake					
		function, rear disc brake, front brake lever: O left O right		29			
		parking brake SHIMANO rear wheel V-Brake with thumblever		5			
		one-hand operation for brakes and drivetrain includes RIDEREVER hydraulic coupled brake, AVID BB7 disc brake					
		with parking brake function, mounting the controls: O left O right		51			
		light wire routing only twin wires routed through the frame for hub dynamo		10			
		lighting system B&M EYRO rechargeable up to 30 lux, headlight rechargeable with USB, battery-powered rear light		11			
		B&M Toplight 2C permanent					
		lighting system B&M IQ-XS friendly for E-drive LED headlight B&M IQ-XS friendly, up to 80 lux, rear light B&M		21			
		Toplight 2C DC					
		lighting system B&M IQ-X for E-drive B&M IQ-X up to 150 Lux, rear light B&M Toplight 2C DC		29			
		lighting system SON xs-m disc dynohub/IQ-X with stand light, daytime running light and brake light, SCHMIDTS		75			
		ORIGINAL NABENDYNAMO, B&M IQ-X headlight, up to 100 lux, B&M Toplight 2C plus rear light					
		indicator lights system WingBling only in conjunction with electric drive		66			
	-	rear rack 10 mm / 0.4" tube, black powder coating, max. load 25 kg / 55 lbs		8			
		side bag mount mounting for handlebar bags, fixed to the frame, maximum load 5 kg / 11 lbs, left and right, incl. ring clamp, unmounted, folding function limited, bike can no longer be pulled on wheels (bags not included)		15			
		mudguard set HP Trikefender front 60 mm / 2.4" width, rear SKS 53 mm / 2.1" with spoiler, black		32			
		clipless pedals SHIMANO PD-T8000 lightweight, multi-purpose pedal for normal and SPD shoes		8			
	—	handrest with retaining strap comfortable hand support mounted on handlebar					
		mounting side of handrest: O left O right					
ries		handrests left and right with one retaining strap with one retaining strap, mounting side of retaining strap: O left					
SSO		O right		20			
accessories		handrests left and right comfortable hand support, mounted on handlebar, removable cushion		15			
Ű		standing-up aid support with grip for easy entry and exit from the trike, knuckle mounted, price per side,		9			
		O left O right O pair		7			
		water bottle set HP VELOTECHNIK 2 x 0.6 PE-bottle with HP print, with bottle cages, mounted		7			
		rear mirror MIRRYCLE with barend mounting, also computer mount O left O right		6			
		rear mirror MIRRYCLE both sides barend mounting left and right		13			
		rear mirror B&M E wide view angle, easy to adjust, knuckle mounting O left O right		8			
		rear mirror B&M E both sides left and right knuckle mounting		16			
		flag HP VELOTECHNIK double-sided print, with reflective strip		2			
		universal mount for accessories Mounting in handlebar end (twist shifters) or on barend shifter, Ø 22,2 mm / 0.87" tube holder for accessories like phone holder / GPS devices / bell, max. load 400 grams / 0,88 lbs, unmounted		4			
		speedometer mount for computers or battery lights, incl. sensor bracket for front wheel		2			
		air horn AIRZOUND XL about 30-115 dB, not mounted Streamer clear front fairing, with quickmount system, incl. assembly (not w/PINION and SHIMANO STEPS)		3			
		transport cover suitable for all folded HP VELOTECHNIK trikes, nylon fabric		65			
		frame lock AXA Victory with removable key, without chain, black		8			
	-	chain for frame lock AXA length 100 cm / 39.4"	├ ── 	2			

Suggested retail prices in EURO including German VAT (19 %) plus shipping. Please contact your authorized HP VELOTECHNIK dealer for details and ordering.