

	×	ltem	sugg. reta \$
Ge	ekk	o fxs foldable recumbent trike for children and special ability use 20"/20" (GES)	
		Gekko fxs basic model SHIMANO Nexus Premium internal gear hub 8 speed, 135 mm / 5,3" 32 teeth crankset, AVID BB7	
	×	mechanical disc brakes, B&M EYRO lighting system, rear rack, mudguards Trikefender, pedals with heel strap and foot clamp,	5,330.0
		OrthoFlex seatmesh with individual upholstery, adjustable retention belt system	
Ge		o fxs options extra charge	
		standard colour magma red	0.0
	_	single custom colour according to RAL-colour chart: (please specify)	229.0
		length fitting service: distance center of bottom bracket to end of main frame, look at the marking on the skale cm	0.0
0		front boom quickadjust compensates extra chain length when front boom is adjusted, with quick release levers, ca. 35 cm / 14" adjustment range, incl. adjustable length upper chain protection tube	249.0
frame		long handlebars 6 cm / 2.4" higher grip position	25.0
fra		headrest for meshseat adjustable in height and angle, with quick release lever	189.0
		pelvic support belt for pelvis support on HP VELOTECHNIK recumbent trikes with meshseat, not mounted	279.0
		chest support belt for upper body support on HP VELOTECHNIK recumbent trikes with meshseat, not mounted	279.0
		adjustable end stops allow exact positioning of the seat	19.0
		rain cover for seats, ripstop nylon fabric, blue	25.0
		drivetrain SHIMANO Nexus 8 Premium 8 speed, internal gear hub with twist shifter (basic specification)	0.0
		drivetrain STURMEY ARCHER Tripleshift 30 30 speed, SHIMANO Deore XT rear derailleur, MICROSHIFT /	
		STURMEY ARCHER barend shifters, STURMEY ARCHER 3 speed internal gear hub, SHIMANO XT cassette 11-36 teeth,	239.0
		crankset 5.3" crank length and 32 teeth chainring, double sided chainwheel disc	
		drivetrain ROHLOFF Speedhub/14 14 speed internal gear hub, black, long twist shifter	2,190.0
۲		E-drive SHIMANO STEPS E5000 Nexus Di2 SHIMANO Nexus 8 speed Di2 gear hub, Li-Ionen battery 418 Wh, 2 A	2,640.0
trai		charger, push assist 4 mph , maximum assistance speed: O 9 mph O 16mph	
drivetrain		E-drive SHIMANO STEPS EP801 Cargo ROHLOFF up to 20 mph, incl. ROHLOFF 14 gear interneal gear hub, Li-lonen battery 418 Wh, push assist 4 mph, only with 6.1" crank	5,250.0
p		E-drive NEODRIVES Z20 with MICROSHIFT10 up to 16mph, 10-speed shift MICROSHIFT XLE, Li-lonen battery 576	
		Wh, push assist forward and backwards, Display position: O above handlebar O side of handlebar; max. speed O 9 mph O	3,820.0
		16 mph	-,
		big battery pack SHIMANO STEPS Li-Ionen battery, 630 Wh, fast charger with 4 A	449.0
		shorter / longer cranks O 15 mm / 4,5" O 155 mm / 6,1" instead of 135 mm / 5,3"	25.0
		tire exchange from SCHWALBE Tryker 40 mm / 1.6" to Marathon Plus 47 mm / 1.8"	49.0
		disc brakes AVID BB7 mechanical, separate brake per front wheel, children levers (basic specification)	0.0
		disc brakes SHIMANO BR-MT200 hydraulic, separate brake per front wheel	0.0
		disc brakes AVID BB7 coupled front brakes, mechanical, rear disc brake, parking brake function, lever reach not	199.0
	1.	adjustablefront brake lever: O left O right	199.0
ses		hydraulic disc brakes RIDEREVER coupled hydraulic, coupled front brakes with one-hand operation and parking brake function, rear disc brake, front brake lever: O left O right	329.0
brakes		disc brakes SHIMANO XT hydraulic, separate brake per front wheel, lever reach adjustable	269.0
		parking brake SHIMANO rear wheel V-Brake with thumblever	65.0
		one-hand operation for brakes and drivetrain includes coupled AVID BB7 front disc brake, AVID BB7 disc brake with	
		parking brake function rear, mounting the controls: O left O right	379.0
		one-hand operation for brakes and drivetrain includes hydraulic coupled front brake, AVID BB7 disc brake with parking brake function rear, mounting the controls: O left O right	559.0
		or and function rear, mounting the controls. O feet O fight	

ekko^{ks}

Н	
VELOTE	

order sheet

order sheet

	5	
a	5	
1	Ŋ	
6		
Ľ	ĩ	
2		
(J	
()	
Ζ.	1	
(2	

	×	Item	sugg. retail \$
ac	ce	sories Surcharges, additional accessories on the "comfort and rehab options" order form	
		lighting system rechargeable/EYRO up to 30 Lux, rechargeable headlight and sensor rearlight	0.00
		lighting system SON xs-m disc dynohub/IQ-X parking light front and rear, SCHMIDTS ORIGINAL NABENDYNAMO hubdynamo, LED headlight B&M IQ-X, daytime running lights, up to 100 Lux, rear light B&M Toplight Flat S plus with brake light	639.00
		B&M IQ-XS friendly lighting system for E-drive LED-headlight B&M IQ-XS friendly, powered by E-bike battery, up to 80 Lux, rear light B&M Toplight 2C DC	45.00
		indicator lights system WingBling only in conjunction with electric drive	739.00
	×	rear rack 10 mm / 0.4" tube, black powder coating, max. load 25 kg / 55 lbs	0.00
	×	mudguard set HP Trikefender front 60 mm / 2.4" width, rear SKS 53 mm / 2.1" with spoiler, black	0.00
		pedals with heelstrap and foot clamp left and right, size range: O 22 - 28 cm / 8 - 11" (basic specification) O 27 - 34 cm / 11 - 14"	0.00
		clipless pedals SHIMANO PD-T8000 lightweight, multi-purpose pedal for normal and SPD shoes	0.00
		ErgoPedal single sided other side pedal with heelstrap and foot clamp, mounting side of ErgoPedal: O left O right size: O 7,9" - 11" O 10,6" - 13,4"	45.00
		ErgoPedal left and right size: O 7,9" - 11" O 10,6" - 13,4"	109.00
		ErgoPedal with safety release single sided incl. one SPD-pedal SHIMANO PD-A530, adjustable position, joint-friendly freedom of movement +/- 3 degrees, other side pedal with heelstrap and foot clamp, mounting side of ErgoPedal with safety	115.00
		release: O left O right size: O 7,9" - 11" O 10,6" - 13,4" ErgoPedal with safety release left and right adjustable position, joint-friendly freedom of movement '+/- 3 degrees, size: O 7,9" - 11" O 10,6" - 13,4"	229.00
ies		ErgoPedal with calf brace single sided other side pedal with heelstrap and foot clamp, mounting side of ErgoPedal: O left O right size: O 7,9" - 11" O 10,6" - 13,4"	289.00
accessories		ErgoPedal with calf brace left and right size: O 7,9" - 1 " O 10,6" - 13,4"	580.00
Sce		handrest with retaining strap comfortable hand support mounted on handlebar	
ac		mounting side of handrest: O left O right	119.00
		handrests left and right with one retaining strap with one retaining strap mounting side of retaining strap: O left O right	219.00
		handrests left and right comfortable hand support, mounted on handlebar, removable cushion	169.00
		walking aid mount single sided easy fixing and safety clip, mounting side: O left O right	99.50
		walking aid mounts left and right easy fixing and safety clip	199.00
		standing-up aid support with grip for easy entry and exit from the trike, knuckle mounted, price per side, O left O right O pair	104.50
		companion bar for active steering and braking, incl. brake for companion, not compatible with standing-up aid left, limited folding functionality, installation on left hand side	439.00
		water bottle set HP VELOTECHNIK 2 x 0.6 PE-bottle with HP print, with bottle cages, mounted	79.00
		rear mirror B&M E wide view angle, easy to adjust, knuckle mounting O left O right	89.00
		rear mirror B&M E both sides left and right knuckle mounting	178.00
		rear mirror MIRRYCLE with barend mounting, also computer mount O left O right	65.00
		rear mirror MIRRYCLE both sides barend mounting left and right	130.00
		flag HP VELOTECHNIK double-sided print, with reflective strip	29.00
		universal mount for accessories to be mounted on the handlebar end (with twist shifters) or on the barend shifter, Ø 0.87" tube holder for accessories like mobile phone holder / GPS devices or bell, max. load 0.88 lbs, unmounted	49.00
		speedometer mount for computers or battery lights, incl. sensor bracket for front wheel	29.00
		transport cover suitable for all folded HP VELOTECHNIK trikes, nylon fabric	99.00

All prices in US\$. The MSRP includes duties and shipping, excluding applicable sales tax. This form is valid for US customers only.

Our general terms and conditions shall apply for all orders. Please contact your authorized HP Velotechnik dealer for details and ordering.